

# GALAXY2R™

## TWO RAM BALERS

- Scrap Dealers
- MRF's
- Recycling Centers
- Distribution Centers
- Large Paper & Plastic Processors



- ▼ Advanced Structural Engineering & Construction
- ▼ Efficient, High Performance Power Packs
- ▼ More than 57 Models to Choose From
- ▼ Latest Electronics Technology
- ▼ Computerized Diagnostics
- ▼ Multi-Material Processing
- ▼ CAD Designed & Documented

# GALAXY2R™

[TWO RAM BALERS]

## Features and Benefits



1. **NexDoor™** – Multi-purpose door serves as a bale separator, bale release, bale clamp and allows for variable bale dimensions.



1a. **Automatic Wire Tier with wire dispenser.**

2. **High-efficiency Power Unit** – Power unit available with 30–2x100 HP TEFC motors, features flooded suction pumping system with high-flow hydraulic manifold, 10 micron filtration system, pressure and current transducers, separate cooling & tier circuit and air-to-oil cooler.



3. **Adjustable Shear Beam** – The body shear blades are adjustable from the exterior of the machine.



4. **NEXGEN® Construction.**


**Factory Start-Ups** – Trained NEXGEN personal are on-site for start-up and training your personnel on operating the baler.



5. **Maestro™ Touch-Screen Operator Interface** – Allen Bradley Micrologix 1500 PLC programmable controller features automatic and manual controls, diagnostics and bale set-up functions.




6. **Upper & Lower Infrared Actuators** – Upper infrareds are located on the access door and are adjustable the entire height of the feed hopper.



7. **Shear Blades** – Ram shear blade is replaceable and reversible. Body shear blade is serrated, adjustable and replaceable.

7a. **Replaceable Liners** – Replaceable tongue & groove liners provide superior wear resistance.



8. **Laser Positioning**

**Full Penetration** – Is standard on every model to fully compress material with every stroke allowing for denser bales

### Narrow Models:

Charge Box Openings  
Width: 43"  
Lengths: 57", 70", 84", 102"

### Wide Models:

Charge Box Openings  
Width: 60"  
Lengths: 70", 84", 102"

Authorized Distributor:



® P.O. Box 1798  
Vernon, AL 35592-1798 USA  
(205) 695-9105 • fax (205) 695-7250  
**1-800-633-8974**

Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI Regulation Z245.5 and all OSHA standards. Products must be used with safe practice and in accordance with said regulations and standards.

